



Composite Bonding Tape

8901

Technical Data

June, 2005

Product Description 3M™ Composite Bonding Tape 8901 is a high temperature tape with a silicone adhesive for use in composite bagging operations or to help remove flashing after bonding. This tape is designed to provide clean removal during masking operations involving high temperatures and pressure.

Product Construction	Backing	Adhesive	Color
	Polyester	Silicone	Blue

Typical Physical Properties

Note: The following technical information and data should be considered representative or typical only, and should not be used for specification purposes.

		ASTM Test Method
Adhesion to Steel:	32 oz./in. width (35 N/100 mm)	D-3330
Tensile Strength at Break:	28 lbs./in. width (490 N/100 mm)	D-3759
Elongation at Break:	115%	D-3759
Total Tape Thickness:	2.6 mils (0.06 mm)	D-3652
Temperature Use Range:	Up to 400°F (204°C)	

Application Ideas

- Composite and metal bonding as it removes cleanly from stainless steel, anodized aluminum and glass after a 5 hour bake cycle at 350°F (177°C).
- Masking edges of overlap seams in metal bonding process where excess epoxy (“flash”) flows onto tape as clean-up is complete upon tape removal.
- Holding parts or vacuum bags during bonding process.
- Masking parts for powder coat painting.
- Splicing silicone treated materials.

3M™ Composite Bonding Tape

8901

Storage Store under normal conditions of 70°F (21°C) and 50% R.H. in the original carton.

Shelf Life To obtain best performance, use this product within one year from date of manufacture.

Product Use All statements, technical information and recommendations contained in this document are based upon tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method of application.

Warranty and Limited Remedy Unless stated otherwise in 3M's product literature, packaging inserts or product packaging for individual products, 3M warrants that each 3M product meets the applicable specifications at the time 3M ships the product. Individual products may have additional or different warranties as stated on product literature, package inserts or product packages. 3M MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's application. If the 3M product is defective within the warranty period, your exclusive remedy and 3M's and seller's sole obligation will be, at 3M's option, to replace the product or refund the purchase price.

Limitation of Liability Except where prohibited by law, 3M and seller will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

ISO 9001:2000

This product was manufactured under a 3M quality system registered to ISO 9001:2000 standards.

3M

**Industrial Business
Industrial Adhesives and Tapes Division**

3M Center, Building 21-1W-10, 900 Bush Avenue
St. Paul, MN 55144-1000
800-362-3550 • 877-369-2923 (fax)
www.3M.com/industrial



*Recycled Paper
40% pre-consumer
10% post-consumer*

Printed in U.S.A.
©3M 2005 70-0704-3031-2 (6/05)